

# E7515W

## UXM Wireless Connectivity Test Platform

Wi-Fi / 5G NR / LTE / 380MHz to 7.125GHz

### All-In-One Wi-Fi Test Unit

The new Keysight E7515W UXM Wireless Connectivity Test Platform extends the UXM Platform – the world's most powerful 5G network emulator – to support extensive Wi-Fi testing. This system performs Wi-Fi RF to Application, and Wi-Fi to Cellular interworking testing of both Wi-Fi clients (STAs) and Access Points (APs).



The standalone E7515W greatly simplifies the user's test bed and offers best in class capabilities, with powerful automation, extensive configuration, and repeatable debug-able results. This is a top-of-the-line product for serious testing.

# Vector Signal Analyzer Performance

E7515W-00A

Frequency and time specification	
Operating frequency range <ul style="list-style-type: none"> <li>• Default</li> <li>• E7515W-507</li> </ul>	<ul style="list-style-type: none"> <li>• 380 MHz to 6 GHz</li> <li>• 380 MHz to 7.125 GHz</li> </ul>
Frequency setting resolution	1 Hz
Frequency accuracy	See Time base specifications
VSWR all RF_in / RF_out	
380 MHz to 600 MHz	< 1.5 nominal
> 600 MHz to 2GHz	< 1.5 nominal
> 2GHz to 4GHz	< 1.5 nominal
> 4GHz to 6GHz	< 1.5 nominal
> 6 GHz to 8 GHz	< 1.5 nominal
Amplitude and range specifications	
CW level accuracy	
+5 to +30dBm for all Receiver ports <ul style="list-style-type: none"> <li>380 MHz to 3GHz</li> <li>&gt; 3GHz to 4.2GHz</li> <li>&gt; 4.2GHz to 6GHz</li> <li>&gt; 6 GHz to 7.125 GHz</li> </ul>	<ul style="list-style-type: none"> <li>±0.45 dB nominal</li> <li>±0.45 dB nominal</li> <li>±0.45 dB nominal</li> <li>±0.45 dB nominal</li> </ul>
-60 to +5dBm for all Receiver ports <ul style="list-style-type: none"> <li>380 MHz to 3GHz</li> <li>&gt; 3GHz to 4.2GHz</li> <li>&gt; 4.2GHz to 6GHz</li> <li>&gt; 6 GHz to 7.125 GHz</li> </ul>	<ul style="list-style-type: none"> <li>±0.3 dB typical</li> <li>±0.3 dB typical</li> <li>±0.3 dB typical</li> <li>±0.3 dB typical</li> </ul>
-40 to +5dBm for all receiver ports <ul style="list-style-type: none"> <li>380 MHz to 4.2GHz</li> <li>4.2 GHz to 7.125GHz</li> </ul>	<ul style="list-style-type: none"> <li>±1.23 dB warranted</li> <li>±1.23 dB warranted</li> </ul>
Level flatness	
Over 100 MHz bandwidth relative to central frequency <ul style="list-style-type: none"> <li>380 MHz to 3GHz</li> <li>&gt; 3GHz to 4.2GHz</li> <li>&gt; 4.2GHz to 6GHz</li> <li>&gt; 6 GHz to 7.125 GHz</li> </ul>	<ul style="list-style-type: none"> <li>±0.25 dB typical</li> <li>±0.25 dB typical</li> <li>±0.25 dB typical</li> <li>±0.3 dB typical</li> </ul>
Over 800 MHz bandwidth relative to central frequency <ul style="list-style-type: none"> <li>380 MHz to 3GHz</li> <li>&gt; 3GHz to 4.2GHz</li> <li>&gt; 4.2GHz to 6GHz</li> <li>&gt; 6 GHz to 7.125 GHz</li> </ul>	<ul style="list-style-type: none"> <li>±0.35 dB typical</li> <li>±0.35 dB typical</li> <li>±0.35 dB typical</li> <li>±0.35 dB typical</li> </ul>
Over 1600 MHz bandwidth relative to central frequency <ul style="list-style-type: none"> <li>380 MHz to 3GHz</li> <li>&gt; 3GHz to 4.2GHz</li> <li>&gt; 4.2GHz to 6GHz</li> <li>&gt; 6 GHz to 7.125 GHz</li> </ul>	<ul style="list-style-type: none"> <li>±0.4 dB typical</li> <li>±0.4 dB typical</li> <li>±0.4 dB typical</li> <li>±0.4 dB typical</li> </ul>
Noise spectral density all RF_in/RF_out ports <ul style="list-style-type: none"> <li>RF_out set to max DL power</li> <li>RF_out set to OFF               <ul style="list-style-type: none"> <li>380 MHz to 6 GHz</li> <li>6 GHz to 7.125 GHz</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>&lt; -150 dBm/Hz nominal</li> <li>&lt; -150 dBm/Hz nominal</li> <li>&lt; -150 dBm/Hz nominal</li> </ul>
Maximum CW input level <ul style="list-style-type: none"> <li>RF_in/ RF_out ports</li> </ul>	+29 dBm nominal

# Vector Signal Generator Performance

E7515W-00A

Frequency and time specification	
Operating frequency range <ul style="list-style-type: none"> <li>• Default</li> <li>• E7515W-507</li> </ul>	<ul style="list-style-type: none"> <li>• 380 MHz to 6 GHz</li> <li>• 380 MHz to 7.125 GHz</li> </ul>
Frequency setting resolution	1 Hz
Frequency accuracy	See Time base specifications
VSWR all RF_in / RF_out	
380 MHz to 600 MHz	< 1.25 nominal
> 600 MHz to 2GHz	< 1.25 nominal
> 2GHz to 4GHz	< 1.50 nominal
> 4GHz to 6GHz	< 1.50 nominal
> 6 GHz to 7.125 GHz	< 1.50 nominal
Amplitude and range specifications	
<b>CW output level accuracy</b> -110dBm to -50dBm for all Transmitter ports	
380MHz to 3GHz	±0.69 dB typical
> 3GHz to 4.2GHz	±0.5 dB typical
> 4.2 GHz to 6 GHz	±0.5 dB typical
> 6 GHz to 7.125 GHz	±0.5 dB typical
-50dBm to -3dBm for all Transmitter ports	
380MHz to 4.2GHz	±0.35 dB typical
> 4.2GHz to 6GHz	±0.4 dB typical
> 6 GHz to 7.125 GHz	±0.4 dB typical
-50dBm to -3dBm for all Transmitter ports	
380MHz to 4GHz	±1.23 dB warranted / ±0.35 dB typical
4.2 GHz to 7.125 GHz	±1.23 dB warranted / ±0.4 dB typical
Output level setting resolution	
<b>Output level settling time</b>	
No amplitude change, frequency change within band	±1.0 dB within 100µs nominal
Amplitude change, no frequency change	±0.1 dB within 25 µs nominal
Frequency change	±0.1 dB within 100ms nominal
<b>Output Level flatness</b>	
Over 100 MHz bandwidth relative to central frequency	
380 MHz to 3GHz	±0.15 dB typical
> 3GHz to 4.2GHz	±0.25 dB typical
> 4.2GHz to 6GHz	±0.35 dB typical
> 6 GHz to 7.125 GHz	±0.4 dB typical
Over 800 MHz bandwidth relative to central frequency	
380 MHz to 3GHz	±0.2 dB typical
> 3GHz to 4.2GHz	±0.35 dB typical
> 4.2GHz to 6GHz	±0.45 dB typical
> 6 GHz to 7.125 GHz	±0.45 dB typical
Over 1600 MHz bandwidth relative to central frequency	
380 MHz to 3GHz	±0.2 dB typical
> 3GHz to 4.2GHz	±0.35 dB typical
> 4.2GHz to 6GHz	±0.45 dB typical
> 6 GHz to 7.125 GHz	±0.45 dB typical
<b>Wideband noise floor (for DL at max CW power)</b>	-140dBm/Hz nominal
<b>Maximum reverse power (Operating)</b> All RF_in/ RF_out ports	+29 dBm average power, nominal +42 dBm peak power, nominal

<b>Maximum reverse power (Damage)</b> All RF_in/ RF_out ports	+29 dBm average power, nominal +42 dBm peak power, nominal
<b>Maximum output power</b> All RF_in/RF_out ports	+7dBm (PEP) up to 4 GHz +5dBm (PEP) up to 6 GHz 0 dBm (PEP) up to 12 GHz -5 dBm (PEP) up to 15 GHz
<b>Phase noise</b> 380MHz to 7.125GHz	-100 dBc at 10kHz, nominal -105 dBc at 100kHz, nominal -120 dBc at 1MHz, nominal
<b>Harmonics</b>	
Attenuation of 2 <sup>nd</sup> harmonic all RF_in/ RF_out ports 380 MHz to 4 GHz, power < -10 dBm 4 to 6 GHz, power < - 10 dBm 6 to 7.125GHz, power < -10 dBm	> 30 dBc nominal > 30 dBc nominal > 30 dBc nominal
Attenuation of 3 <sup>rd</sup> harmonic all RF_in/ RF_out ports 380 MHz to 4 GHz, power < -10 dBm 4 to 6 GHz, power < - 10 dBm 6 to 7.125GHz, power < -10 dBm	> 40 dBc nominal > 40 dBc nominal > 40 dBc nominal

# Instrument Specifications

Input power requirements	
Voltage and frequency	100/120/220/240 VAC, 50/60 Hz, nominal
Power consumption (Fully loaded configuration)	1800 W max
Additional Specifications	
Dimensions (H x W x L)	
Without feet and handles	309 mm x 436 mm x 554 mm
With feet and handles	323 mm x 453 mm x 554 mm
Weight	
Fully loaded configuration	E7515W-00A: 45 kg
Operating temperature	+10 to +40 °C, 30 g/m <sup>3</sup> absolute humidity, 5 to 85% non-condensing relative humidity
Storage temperature	-40 to +70 °C, 50 g/m <sup>3</sup> absolute humidity, 5 to 85% non-condensing relative humidity
Altitude	Up to 2000 m
EMC	<p>Complies with European EMC Directive 2004/108/EC</p> <ul style="list-style-type: none"> <li>- IEC/EN 61326-1</li> <li>- CISPR Pub 11 Group 1, class A</li> <li>- AS/NZS CISPR 11</li> <li>- ICES/NMB-001</li> <li>- This ISM device complies with Canadian ICES-001.</li> <li>- Cet appareil ISM est conforme a la norme NMB-001 du Canada.</li> <li>- South Korean Class A EMC declaration: This equipment is Class A suitable for professional use and is for use in electromagnetic environments outside of the home.</li> <li>- A급 기기 (업무용 방송통신기 자재)</li> </ul> <p>이 기기는 업무용(A급) 전자파 적합기기로서 판매자 또는 사용자는 이 점을 주의하시기 바라며, 가정외의 지역에서 사용하는 것을 목적으로 합니다.</p>
Mechanical resistance	EN60068-2-6, EN60068-2-27, EN60068-2-64
Safety	<p>Complies with European Low Voltage Directive 2006/95/EC</p> <ul style="list-style-type: none"> <li>- IEC/EN 61010-1, 3rd edition</li> <li>- Canada: CAN/CSA C22.2 No. 61010-1012</li> <li>- USA: UL std no. 61010-1, 3rd Edition</li> <li>- Acoustic statement (European Machinery Directive 2002/42/EC, 1.7.4.2u)</li> </ul> <p>Acoustic noise emission, LpA &lt;70 dB, Operator position, Normal operation mode, Per ISO 7779</p>
RF Connections	
RF_in/ RF_out ports	N-type female, 50 Ω nominal
Other connectors and interfaces	
Display/Manual user interface	15.4 in (391 mm) active matrix, color, 1280 x 800-pixel resolution TFT-LCD flat panel display with touch panel controls
USB ports	
Front panel	2x USB 2.0
Rear panel	2x USB 3.0
LAN (local area network) ports (control)	One external, 1 Gbps, LAN port rear panel One external, 1 Gbps, LAN port front panel
LAN (local area network) ports (data)	40 Gbps connectivity (rear panel) (E7515W-00A)
QSFP+ connectivity	4 ports, in E7515W-00A
Digital data acquisition	
General memory budgets and considerations	
Available memory (capture and/or playback)	16GB total

Signal acquisition	
IQ data acquisition channels	8 in E7515W-00A
Samples rates	30.72, 61.44, 122.88, 245.76 and 491.52 MSa/s
Maximum sample storage	1GSa per UL RF_in port
Maximum capture size	4GB per channel
Trigger control	Immediate and external
Analyzer bandwidth	20 MHz bandwidth (30.72 MSa/s) 50 MHz bandwidth (61.44 MSa/s) 100 MHz bandwidth (122.88 MSa/s) 200 MHz bandwidth (245.76 MSa/s) 400 MHz bandwidth (491.52 MSa/s)
<b>Gaussian noise generator</b>	
Independent channels	16
RF_IN/ RF_OUT port	Configured via RFIO
Digital frequency offset	-800MHz+BW <sub>Noise</sub> /2 to 800MHz-BW <sub>Noise</sub> /2 in E7515W-00A
<b>Continuous wave generation</b>	
Independent channels	8
RF_IN/ RF_OUT port	Configured via RFIO
Digital frequency offset	-800 to 800 MHz in E7515W-00A
<b>Arbitrary wave generation</b>	
Independent channels	8
Antenna output	Configured via RFIO
Digital frequency offset	-800MHz+BW <sub>Signal</sub> /2 to 800MHz-BW <sub>Signal</sub> /2 in E7515W-00A
Memory allocation for arbitrary wave generation	16 GB (shared with digital data acquisition)
Waveform sampling rate	
Bandwidth 20MHz	30.72 MSa/s
Bandwidth 50MHz	61.44 MSa/s
Bandwidth 100MHz	122.88 MSa/s
Bandwidth 200MHz	245.76 MSa/s
Bandwidth 400MHz	491.52 MSa/s
Maximum waveform file size	4 GB
Waveform play modes	Single, continuous
<b>Time base</b>	
Standard frequency reference	
Maximum frequency drift	± 50 ppb/2 years
Warm-up time	30 min
<b>External clock time reference</b>	
Connector type	SMA connector 10 MHz IN, rear panel
Frequency	
Sine wave	10 MHz
Square wave (greater than 40% ON duty cycle)	10 MHz
Input voltage range	0.4 to 2 Vpp
Impedance	50 Ω nominal
<b>Format alignment trigger</b>	
External connector	SMA Channel 0
Trigger duration	Samples resolution = $(1 / 30.72) \times 10^{-6}$ 1 to $2^{31}-1$ samples
Trigger offset delay	In terms of 1/6 of the period of the sample
Trigger period	1 to $2^{31}-1$ samples
External connector	Up to 8, SMA connector (Input, Output)
Arm channel for receiving trigger	Only input channels
External trigger generation	Only output channels
<b>Base band fader</b>	
Fading blocks (100 MHz)	40
<b>Warranty and calibration</b>	
Standard warranty	One year
Recommended calibration cycle	One year

# 5G NR Measurements

Modulation and channels	
Signal structure	TDD, FDD (with appropriate software license)
Signal bandwidth	100MHz
EVM performance (-10 dBm channel power, 256 QAM, 1 CC 100 MHz)	
380 MHz to 3 GHz	0.70%, typical
3 to 6 GHz	0.70%, typical

# Definitions and Conditions

The specifications in this document apply to E7515W UXM Wireless Connectivity Test Platforms with following configuration identifiers:

UXM Config Identifier	Description
E7515W-00A	E7515W UXM Wireless Connectivity Test Platform, configuration 00A

The test set will meet its specifications when

- The test set is within its calibration cycle.
- The test set has been stored at an ambient temperature within the allowed operating range for at least two hours before being turned on; if it had previously been stored at a temperature range inside the allowed storage range, but outside the allowed operating range.
- The test set has been turned on for at least 30 minutes.

## Specification

Specifications describe the performance parameters covered by the product warranty and are valid from 20 to 30 °C unless otherwise noted.

## Typical

Typical describes additional product performance information that is not covered by the product warranty. It is performance beyond specifications that 95 percent of the units exhibit with a 95 percent confidence level. This data, shown in italics, does not include measurement uncertainty, and is valid only at room temperature, 23 °C.

## Nominal

Nominal values indicate expected performance or describe product performance that is useful in the application of the product but are not covered by the product warranty.

Keysight enables innovators to push the boundaries of engineering by quickly solving design, emulation, and test challenges to create the best product experiences. Start your innovation journey at [www.keysight.com](http://www.keysight.com).