

## P/N: 85902-0102

### Copyright

© 2023, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

### Document identity

Publ. No.: 85902-0102

Commit: 93984

Language:

Modified: 2023-11-01

Formatted: 2023-11-01

### Website

<http://www.flir.com>

### Customer support

<http://support.flir.com>

### Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to [exportquestions@flir.com](mailto:exportquestions@flir.com) with any questions.



<b>Imaging and optical data</b>	
Infrared resolution	640 × 480 pixels
Thermal sensitivity (NETD)	<40 mK, 24° @ +30°C (+86°F)
Field of view (FOV)	24° × 18°
Minimum focus distance	0.15 m (0.49 ft)
Focal length	17 mm (0.67 in)
Spatial resolution (IFOV)	0.7 mrad/pixel
Lens identification	Automatic
f-number	1.3
Image frequency	30 Hz
Focus	<ul style="list-style-type: none"> <li>• One-shot contrast</li> <li>• Motorized</li> <li>• Manual</li> </ul>
<b>Detector data</b>	
Focal plane array/spectral range	Uncooled microbolometer/7.5–14 μm
Detector pitch	12 μm



# FLIR A700 24° Professional Science Kit

P/N: 85902-0102

© 2023, FLIR Systems, Inc.

#85902-0102; r. 93984;

<b>Measurement</b>	
Camera temperature range	<ul style="list-style-type: none"> <li>-20 to 120°C (-4 to 248°F)</li> <li>0 to 650°C (32 to 1202°F)</li> <li>300 to 2000°C (572 to 3632°F)</li> </ul>
Object temperature range and accuracy (for ambient temperature 15–35°C (59–95°F))	<ul style="list-style-type: none"> <li>Range -20 to 120°C (-4 to 248°F):               <ul style="list-style-type: none"> <li>-20 to 100°C (-4 to 212°F), accuracy ±2°C (±3.6°F)</li> <li>100 to 120°C (212 to 248°F), accuracy ±2%</li> </ul> </li> <li>Range 0 to 650°C (32 to 1202°F):               <ul style="list-style-type: none"> <li>0 to 100°C (32 to 212°F), accuracy ±2°C (±3.6°F)</li> <li>100 to 650°C (212 to 1202°F), accuracy ±2%</li> </ul> </li> <li>Range 300 to 2000°C (572 to 3632°F):               <ul style="list-style-type: none"> <li>accuracy ±2%</li> </ul> </li> </ul>
<b>Video/Radiometric streaming RTSP</b>	
Protocol	RTSP
Unicast	Yes
Multicast	Yes
Multiple image streams	Yes
<b>Video streaming</b>	
Image quality	Bit rate set through Camera web
<b>Video streaming, Image source 0:</b>	
Resolution (source 0)	640 × 480 pixels
Contrast enhancement	FSX / Histogram equalization (IR only)
Overlay (source 0)	With / Without
Image source (source 0)	Visual / IR / MSX
Pixel format (source 0)	YUV411
Encoding (source 0)	H.264 / MPEG4 / MJPEG
<b>Video streaming, Image source 1:</b>	
Resolution (source 1)	1280 × 960 pixels
Overlay (source 1)	No
Image source (source 1)	Visual
Pixel format (source 1)	YUV411
Encoding (source 1)	H.264 / MPEG4 / MJPEG
<b>Radiometric streaming</b>	
Resolution (radiometric)	640 × 480 pixels
Source	IR
Pixel format (radiometric)	MONO 16
Encoding (radiometric)	<ul style="list-style-type: none"> <li>Compressed JPEG-LS</li> <li>FLIR Radiometric</li> </ul>
<b>Video/Radiometric streaming GVSP (GigE Vision)</b>	
Protocol	GVSP
Unicast	Yes
Multicast	Yes



# FLIR A700 24° Professional Science Kit

P/N: 85902-0102

© 2023, FLIR Systems, Inc.

#85902-0102; r. 93984;

<b>Video/Radiometric streaming GVSP (GigE Vision)</b>	
Multiple image streams	No, 1 stream only
<b>Video streaming</b>	
<b>Video streaming, Image source 0:</b>	
Resolution (source 0)	640 × 480 pixels
Contrast enhancement	FSX / Histogram equalization (IR only)
Overlay (source 0)	With / Without
Image source (source 0)	Visual / IR / MSX
Pixel format (source 0)	YUV422 or MONO 8
Encoding (source 0)	Un-compressed
<b>Radiometric streaming</b>	
Resolution (radiometric)	640 × 480 pixels
Source	IR
Pixel format (radiometric)	MONO 16
Encoding (radiometric)	<ul style="list-style-type: none"> <li>Temperature linear</li> <li>FLIR Radiometric</li> <li>Compressed JPEG-LS</li> </ul>
<b>Ethernet</b>	
Interface	<ul style="list-style-type: none"> <li>Wired</li> <li>Wi-Fi</li> </ul>
Connector type	<ul style="list-style-type: none"> <li>M12 8-pin X-coded, Female</li> <li>RP-SMA, Female</li> </ul>
Ethernet, purpose	Control, result, image, and power
Ethernet, type	1000 Mbps
Ethernet, standard	IEEE 802.3
Ethernet, communication	<ul style="list-style-type: none"> <li>GigE Vision ver. 1.2</li> <li>Client API GenICam compliant</li> <li>TCP/IP socket-based FLIR proprietary</li> </ul>
Ethernet, power	Power over Ethernet, PoE IEEE 802.3af class 3
Ethernet, protocols	<ul style="list-style-type: none"> <li>IEEE 1588</li> <li>ONVIF-S</li> <li>SNMP</li> <li>TCP, UDP, SNTP, RTSP, RTP, HTTP, ICMP, IGMP, sftp (server), FTP (client), SMTP, DHCP, MDNS (Bonjour), uPnP</li> </ul>
<b>Digital Input/output</b>	
Connector type	M12 12-pin A-coded, Male (shared with external power)
Digital input	2x opto-isolated Vin(low)= 0–1.5 V, Vin(high)= 3–25 V
Digital input, purpose	<ul style="list-style-type: none"> <li>NUC</li> <li>NUC disable</li> <li>Image TAG (Start, Stop, General)</li> <li>Image flow control (acc. SFNC 2.3)               <ul style="list-style-type: none"> <li>Single frame (on trigg)</li> <li>Multiframe (on trigg)</li> <li>Continuous</li> <li>Frame rate</li> <li>ROI</li> </ul> </li> </ul>



# FLIR A700 24° Professional Science Kit

P/N: 85902-0102

© 2023, FLIR Systems, Inc.

#85902-0102; r. 93984;

<b>Digital Input/output</b>	
Digital output	<ul style="list-style-type: none"> <li>• 3x opto-isolated, 0–30 V DC, max. 300 mA (derated to 200 mA at 60C)</li> <li>• Solid state opto relay</li> <li>• 1x dedicated as Fault output (NC)</li> </ul>
Digital output, purpose	<ul style="list-style-type: none"> <li>• Programmatically set</li> <li>• Fault (NC)</li> </ul>
Digital I/O, isolation voltage	500 VRMS
<b>Power system</b>	
Connector type	M12 12-pin A-coded, Male (shared with Digital I/O)
Power consumption	<ul style="list-style-type: none"> <li>• 7.5 W at 24 V DC typical</li> <li>• 7.8 W at 48 V DC typical</li> <li>• 8.1 W at 48 V PoE typical</li> </ul>
External power operation	24/48 V DC 8 W max
External voltage	Allowed range 18–56 V DC
<b>RS-232/485 serial interface</b>	
Connector type	M8 A-coded, Male
Prerequisite for use	ONVIF must be initiated.
Serial communication, purpose	Pan & Tilt control
Serial communication, standard	Pelco D
Serial communication, HW interface	RS232 and RS485 exclusively
Scanlist support	Yes
<b>Wi-Fi</b>	
Connector type	RP-SMA, Female
Standard	IEEE802.11a/b/g/n
Antenna	Dipole antenna 2.4/5 GHz (gain: maximum 2 dBi)
Connection type	Peer to peer (ad hoc) or infrastructure (network)
<b>Environmental data</b>	
Operating temperature range	–20 to 50°C (–4 to 122°F) Cooling plate is needed in temperatures above 40°C (104°F). Maximum camera case temperature: 65°C (149°F)
Storage temperature range	IEC 68-2-1 and IEC 68-2-2, –40 to 70°C (–40 to 158°F) for 16 hours
Humidity (operating and storage)	IEC 60068-2-30/24 hours, 95% relative humidity, 25–40°C (77–104°F)/2 cycles
EMC	<ul style="list-style-type: none"> <li>• ETSI EN 301 489-1 (radio)</li> <li>• ETSI EN 301 489-17 (radio)</li> <li>• EN 61000-4-8 (magnetic field)</li> <li>• FCC 47 CFR Part 15 Class B (emission US)</li> <li>• ISO 13766-1 (EMC - Earth-moving and building construction machinery)</li> <li>• EN ISO 14982 (EMC - Agricultural and forestry machinery)</li> </ul>



# FLIR A700 24° Professional Science Kit

P/N: 85902-0102

© 2023, FLIR Systems, Inc.

#85902-0102; r. 93984;

Environmental data	
Radio spectrum	<ul style="list-style-type: none"><li>FCC 47 CFR Part 15 Class C (2.4 GHz band US)</li><li>FCC 47 CFR Part 15 Class E (5 GHz band US)</li><li>RSS-247 (2.4 GHz and 5 GHz band Canada)</li><li>ETSI EN 300 328 V2.1.1 (2.4 GHz band EU)</li><li>ETSI EN 301 893 V2.1.1 (5 GHz band EU)</li><li>GlTEKI certification number: R201-140447</li></ul>
Encapsulation	IEC 60529, IP 54, IP66 with accessory
Shock	IEC 60068-2-27, 25 g
Vibration	<ul style="list-style-type: none"><li>IEC 60068-2-6, 0.15 mm at 10–58 Hz and 2 g at 58–500 Hz, sinusoidal</li><li>IEC 61373 Cat 1 (Railway)</li></ul>
Safety	IEC 62368-1 (IT equipment audio-visual products)
Corrosion	<ul style="list-style-type: none"><li>ISO 12944 C4 G or H</li><li>EN60068-2-11</li></ul>
Shipping information	
Packaging, type	Cardboard box
Packaging, contents	<ul style="list-style-type: none"><li>Camera with Advanced Image Streaming configuration and 24° lens</li><li>Hard case for FLIR A400/A500/A700 series</li><li>Ethernet cable M12 to RJ45, 2 m</li><li>Ethernet cable M12 to RJ45F, 0.3 m</li><li>Ethernet cable CAT6, 2 m/6.6 ft</li><li>Cable M12 to pigtail, 2 m</li><li>Gigabit PoE injector 16 W, with multi-plugs</li><li>Option, Macro mode 50/71/101 µm for 24°</li><li>Research Studio, Professional Edition - 1 Year Subscription (Online Activation)</li><li>Antenna WLAN 2.4/5 GHz + Wi-Fi</li><li>Option, Visual camera including MSX</li><li>Macro lens 2.0x</li><li>Printed documentation including the username and password for log in to the web interface of the camera</li></ul>
Packaging, weight	4.64 kg (10.2 lb)
Packaging, size	500 × 190 × 370 mm (19.7 × 7.5 × 14.6 in)
EAN-13	7332558026847
UPC-12	845188022884

## Compatible with the following products:

- T300239; IR lens, f=10 mm (42°)
- T300240; IR lens, f=17 mm (24°)
- T300241; IR lens, f=29 mm (14°)
- T300586; IR lens Dual FOV, f=17/29 mm (24°/14°)
- T300095; IR lens, f=70 mm (6°) with case
- T951004ACC; Ethernet cable CAT6, 2 m/6.6 ft.
- T130665ACC; Cooling plate
- T300075ACC; IP hood for lens
- T300163; Hard case for FLIR A400/A500/A700 series
- T300202; Connector cap kit
- T300216; Axxx Accessory kit
- T300218; Two-ball mounting bracket kit
- T300268ACC; A-series connection board
- T911850; Antenna WLAN 2.4/5 GHz + Wi-Fi
- T911850ACC; Antenna for WLAN 2.4/5 GHz



## FLIR A700 24° Professional Science Kit

**P/N: 85902-0102**

© 2023, FLIR Systems, Inc.

#85902-0102; r. 93984;

- T911852ACC; Cable M12 to pigtail, 2 m
- T911853ACC; Cable M12 to pigtail, 10 m
- T911854ACC; Ethernet cable M12 to RJ45, 2 m
- T911855ACC; Ethernet cable M12 to RJ45, 10 m
- T911869ACC; Ethernet cable M12 to RJ45F, 0.3 m
- T911183; Gigabit PoE injector 16 W, with multi-plugs
- T300572; Option, Force password change at first-time use
- T199507; Gigabit PoE injector 15 W
- T199870; Extended Calibration Certificate for A7xx
- 4232535; FLIR Research Studio, Professional Edition - 1 Year Subscription (online activation)
- 4232556; FLIR Research Studio, Professional Edition - Perpetual License (online activation)
- 4232590; FLIR Research Studio, Professional Edition - Perpetual License (USB dongle)
- 4220499; FLIR Research Studio, Standard Edition - 1 Year Subscription (online activation)
- 4220500; FLIR Research Studio, Standard Edition - Perpetual License (online activation)
- 4220646; FLIR Research Studio, Standard Edition - Perpetual License (USB dongle)
- 4232591; FLIR ResearchIR to Research Studio, Professional Edition - 1 Year License Upgrade