

DATA SHEET

Extreme Temperature Probing Solutions for Oscilloscope Measurements

Industry's most comprehensive extreme-temperature chamber
testing solutions for oscilloscopes



- Passive and active probing solutions for extreme environmental testing
- Supports temperature ranges as wide as -55 to +150 °C

Many engineers have a need to monitor their product in an environmental chamber with an oscilloscope probe to verify performance over a wide range of operating temperatures or to determine the cause of failures at high or low temperatures. Until now, testing in extreme temperature ranges required engineers to use probes outside their specified operating temperatures, which can damage probes. Most active or passive probes in the market have a specified operating temperature range anywhere from 0 to 50 °C. However, Keysight Technologies Inc. offers various extreme temperature probing solutions that can be operated over a much wider -40 to +85 °C range or even beyond. This allows you to operate the probe head and the supplied probing accessories inside a temperature chamber with the probe pod and oscilloscope located outside the temperature chamber.

For extended temperature testing with more extreme temperature range measurements, Keysight offers the N5450B InfiniiMax extreme-temperature extension cable with the InfiniiMax Series differential probing system, which gives engineers the ability to probe signals at even wider temperature ranges. When used with the Keysight MX0100A or MX0109A differential solder-in probe head, this solution provides engineers with the widest temperature range coverage of -55 to 150 °C, which is the maximum temperature range specified for automotive-electronics testing.



The MX0100A and MX0109A have undergone a rigorous environmental testing to ensure the probe withstand the following specifications.

Operating temperature range ratings:

- -55 °C dwell, 1,000 hours minimum
- +150 °C dwell, 1,000 hours minimum
- -55 to +150 °C cycles, 1,000 cycles minimum per JEDEC JESD22-A104 revision E (MX0100A)
- -55 to +150 °C cycles, 750 cycles minimum per JEDEC JESD22-A104 revision E (MX0109A)

These Keysight probe heads maintain their specified frequency response (and bandwidth) over the operating temperature range, without any need for compensation or correction. High temperatures may cause the probe components to darken but this does not affect measurement quality.

When accurate and repeatable current measurements inside the chamber are critical over wide temperature ranges, the N2820A/21A high-sensitivity current probe is the best choice, especially for precision current measurement applications. When the user-defined head is used with the N2820A/21A current probe, it provides the industry's highest sensitivity current measurement solution among oscilloscope current probes, going all the way down to 50 µA with a maximum current range of 5 A operating over the temperature range of -55 to 150 °C.



The N2797A 1.5 GHz single-ended active probe is the industry's first low-cost high-impedance active probe for environmental chamber testing of ICs and electronic devices at temperatures ranging from -40 to +85 °C. The probe provides 1.5 GHz of bandwidth and high resistance (1 MΩ) and low capacitance (1 pF) input for low probe loading.



The N7007A 400 MHz passive probe is a low-cost, high impedance passive probe with rugged probe tips for environmental chamber testing from -40 to +85 °C. Its large input impedance (10 MΩ at DC) and wide input voltage range (1,000 Vdc + peak AC CATII) makes the probe ideal for a broad range of general purpose extreme temperature applications.



The N7013A is a 70 cm long extreme temperature extension kit compatible with four of Keysight's medium- and high-voltage differential active probes including the N2790A, N2791A, N2792A and N2818A. These probes are typically used in power supply testing applications, as well as testing automotive differential buses including CAN, CAN FD, and FlexRay. With the N7013A extension kit, the extension cables and connection adapters can be extended into the environmental chamber under extreme-temperature conditions ranging from -40 to +85 °C.



This extreme temperature probing solution provides an ideal solution for engineers working with the semiconductor, consumer, wireless mobile devices, automotive electronics, and computer industries who need to validate and characterize their designs while operating within extreme temperature ranges. Keysight now offers the broadest selection of extreme-temperature oscilloscope probing solutions in the market.

There are different bandwidths, temperature ranges and test cycle numbers depending on which probe head/tip you select to use.

Probes and accessories	Signal measurement type	Max bandwidth	Temperature range	Test cycle numbers
MX0109A differential solder-in probe head + InfiniiMax III 2803A	Single-ended or differential (or common mode with InfiniiMax III+ amp)	26 GHz	-55 to +150 °C	1000+
MX0100A micro solder-in probe head + InfiniiMax II 1169B	Single-ended or differential	12 GHz	-55 to +150 °C	1000+
N2836A differential solder-in probe head + InfiniiMax III N2803A	Single-ended or differential voltage	26 GHz	-40 to +85 °C	1000+
N5381B differential solder-in probe head + InfiniiMax II 1169A	Single-ended or differential voltage	12 GHz	-40 to +85 °C	1000+
E2677A differential solder-in probe head + InfiniiMax II 1169A	Single-ended or differential voltage	12 GHz	-25 to +80 °C	1000+
E2678A differential socket probe head + InfiniiMax II 1169A	Single-ended or differential voltage	12 GHz	-25 to +80 °C	
N5425A ZIF head + N5426A tip + InfiniiMax II 1169A	Single-ended or differential voltage	12 GHz	-25 to +80 °C	
N5425B ZIF head + N5426A tip + InfiniiMax II 1169A	Single-ended or differential voltage	12 GHz	-40 to +85 °C	500+
N2797A single-ended active probe	Single-ended voltage	1.5 GHz	-40 to +85 °C	
N7007A passive probe	Single-ended	400 MHz	-40 to +85 °C	
N7013A differential extension kit	Differential	70 MHz with N2818A, N2792A, N2790A, 25 MHz with N2791A	-40 to +85 °C	
N2820A current probe with user defined head and silicon jacketed hook-up cable	Single-ended current	3 MHz (zoom-out)/ 500 kHz (zoom-in)	-55 to +150 °C	

Ordering Information

- For InfiniiMax probe with extension cable + probe head, order one of these configurations below, depending on your probe bandwidth and accessory requirements.
 1. **InfiniiMax I probe:** 1130B/31B/32B/34B InfiniiMax I probe amp + N5450B extension cable + E2677B solder-in head or E2678B socketed head
 2. **InfiniiMax II probe:** 1168B/69B InfiniiMax II probe amp + N5450B extension cable + MX0100A micro head or N5381B solder-in head or N5425B/26A ZIF head/tip or E2677B solder-in head or E2678B socketed head
 3. **InfiniiMax III/III+ probe:** N2800A/01A/02A/03A InfiniiMax III probe amp or N2830A/31A/32A or N7000A/01A/02A/03A, InfiniiMax III+ probe amp + N5450B extension cable + MX0109A solder-in head or N2836A solder-in head
- N2797A 1.5 GHz single-ended active probe
 - For additional accessories, order the N2798A accessory kit for N2797A active probe. It comes with all the standard accessories of the N2797A.
- N2820A 3 MHz high sensitivity current probe.
- N7013A differential extension cable kit includes one each pair of differential extension cables (70 cm long), hook tip adapters and banana-to-socketed tip adapters for connecting to 0.025" sq pins. Order N7014A for an extra banana-to-socketed tip adapter pair.
- N7007A passive probe comes with retractable hook tips, alligator ground leads and spring ground tip. To reorder the accessories, order N7006A spring ground tip, N7008A retractable hook tip or N7009A alligator ground lead.

For more information on the extreme temperature probing solution, go to www.keysight.com/find/extreme.

To learn more about Keysight's probing solutions, go to www.keysight.com/find/probes.



N2797A single-ended

- 1.5 GHz
- 1 M Ω input R
- -40 to +85 °C



N7013A extreme temperature extension kit

- 70 MHz
- For use with N2790A, N2791A, N2792A or N2818A
- -40 to +85 °C



InfiniiMax + N5450B extension cable + probe head

- Differential & SE
- Up to 26 GHz
- 50 k Ω input R
- -55 to +150 °C



N7007A passive probe

- 400 MHz
- 10 M Ω input R
- -40 to +85 °C



N2820A/21A high-sensitivity current probe

- Current
- 3 MHz
- 1.5 G Ω input R
- -55 to +150 °C

Learn more at: www.keysight.com

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at: www.keysight.com/find/contactus

