# PathWave Signal Generation (PWSG) for NR-V2X

Desktop application (2023 release)

# Introduction

NR-V2X is a next-generation vehicle-to-everything (V2X) communication standard, based on 3GPP's 5G NR Sidelink standard with higher performance, flexibility, and reliability for advanced use cases beyond LTE-based Cellular V2X.

Developing and testing emerging standards like NR-V2X is especially challenging. PathWave Signal Generation (PWSG) for NR-V2X helps accelerate the signal creation process with a user interface based on parameterized and graphical signal configuration and tree-style navigation

The Keysight PathWave Signal Generation (PWSG) for NR-V2X is the industry's first 5G NR based V2X signal generation application.

# **Key features**

- Create 3GPP standard compliant NR-V2X signals with channel coding for non-signaling transmitter and receiver testing
- Support Channels and Signals: PSSS, SSSS, PSBCH, PSCCH, PSSCH, PSFCH, CSI-RS, PTRS
- Provide Fixed Reference Channel (FRC) configuration wizard for standard-compliant receiver testing
- One-button generate and download to the supported Keysight Signal Generators

🚸 PATHWAVE 🖷 File - 🗎	System - 🗋 🖻 🗗	
G Home NR-V2X ×		
🖒 Generate 🛓 Generate & Downlo	ad Carrier Waveform Hardware	
+ 0	S-SS/PSBCH PSCCH PSSCH PSFCH CSI-RS	
✓ Carrier 0	✓ General Settings	
BWP Setup		
Channel Setup	Enabled	
	Power Boosting	0 dB
	Transmission Settings Periodicity	
	Number Of S-SSBs	2 ~
	Power Boosting of each S-SSB Block	0,0
	S-SSB Offset In Slot	
	S-SSB Interval In Slot	2
	RB Offset	125
	✓ Payload Settings	
	Channel Coding	
	Scrambling After Channel Coding Auto MIB	
	Payload Data Length	32
	SFN Start	0
	✓ MIB	
	In Coverage	
	TDD Config	0
Instrument License Not Conr	nected	Ģ

Figure 1. PWSG for NR-V2X 2023 Channel Setup User Interface





# **Simplify Standard-Compliant Signal Creation**

Keysight Technologies, Inc. PathWave Signal Generation (PWSG) for NR-V2X application is a flexible signal creation tool that will reduce the time you spend on signal simulation. Quickly and easily generate standard-based and custom NR-V2X signals for component, transmitter, and receiver tests.

#### **Typical measurements**

Component and transmitter test		Receiver test		
ACLR	CCDF	Sensitivity	Blocking	
EVM	Channel Power	Selectivity	Intermodulation	
Occupied Bandwidth				

# **Component and Transmitter Test**

PWSG for NR-V2X application uses waveform playback mode to create and customize waveform files needed to test components and transmitters. Its user-friendly interface lets you configure signal parameters, calculate the resulting waveforms and download files for playback on a vector signal generator or for analysis using the vector signal analysis software. The applications for these test signals include:

- Parametric test of components, such as amplifiers and filters
- Performance characterization and verification of RF sub-systems and transmitters

# **Receiver Test**

PWSG for NR-V2X application enables you to create channel-coded signals for receiver bit-error-rate (BER), block-error-rate (BLER), packet-error-rate (PER), or frame error rate (FER) analysis. Applications include:

- Performance verification and functional test of receivers, during RF/baseband integration and system verification
- Coding verification of baseband subsystems, including FPGAs, ASICs, and DSPs



# **Apply Your Signals in Real-World Testing**

Once you have set up your signals in PWSG for NR-V2X application, you can download them to a variety of Keysight instruments. The PWSG for NR-V2X application complements these platforms by providing a cost-effective way to tailor them to your test needs in design and development.

- Vector Signal Generators
  - MXG/EXG/CXG X-Series
  - VXG (M9384B/M9484C)
- PXIe VXT
  - o M9410A/M9411A
  - M9415A

## **Component and transmitter test**



Figure 2. Typical component test configuration using PWSG Desktop with an X-Series signal generator and analyzer.

PWSG for NR-V2X application generates RF performance optimized V2X waveform which enables you to characterize the power and modulation performance of your components and transmitters. Easy manipulation of a variety of signal parameters, including transmission bandwidth, cyclic prefix, and modulation type, simplifies signal creation.

- Create spectrally-correct signals for channel power, spectral mask, and spurious testing
- Set parameters such as signal bandwidth and channel modulation type (QPSK, 16QAM, 64 QAM, 256QAM) for modulation verification and analysis, such as EVM tests
- View CCDF, spectrum, time domain, and power envelope graphs to investigate the effects of power ramps, modulation formats, power changes, clipping, and other effects on device performance
- Adjust baseband filter to achieve a balance among ACPR, EVM, and narrow resource block spectrum performance



# **Receiver test**



**Figure 3.** Generate receiver test signals for early testing of your receiver with Keysight X-Series signal generators and PathWave Signal Generation.

PWSG for NR-V2X application can be used to generate 5G NR based V2X signals for early testing of receiver system and component hardware. Pair with Keysight signal analyzers and oscilloscopes to evaluate receiver performance at various stages of the receiver chain (RF, IF, and IQ).

NATHWAVE 🗁 File - 🗮 System -	~ °C &				🖽~ @ ?~ _ 🗆 X
G Home NR-V2X ×					
🖒 Generate 🛓 Generate & Download	Car	rier Waveform Hardwa	are		
FRC Config					
	S-SS/PSBCH PSCCH PS	SCH PSFCH CSI-RS			
✓ Carrier 0	Name	Enabled	Slot	BWP	RB Allocation
BWP Setup	PSFCH0			BWP0	0
Channel Setup	✓ General Settings				
	V General Settings				
	Enabled				
	Power Boosting			 0 dB	
	PSFCH HopID			0	
	✓ Resource Allocation				
	Allocated Slots			0	
	First Symbol			11	
	Number of Symbols				
	Bandwidth Part			BWP0 V	
	RB Offset in BWP				
	RB Number				
	Feedback Payload Data			0 ~	
	Harq Ack Value Number of Cyclic Shift Pairs			0 ∽ 6 ∽	
	Cyclic Shift Pair Index			6 ~ 0 ~	
	Cyclic Shift Pair Index			0 •	
10 Spectrum OCDF P					
Instrument License	nd Malle northe	autor turn			an a
IQ <u>Spectrum</u> CCDF					te letert de lett
• — <del>_</del>	10.001101010101010101010101010101010101		COLOR VALUE AND DE LOS V		ACTIVE PROPERTY ALL NO.
-20					· · ·
-40	dour ablidestabilitation de la	and the hand the star of a second second	in the set of the second set of the second	s and a body of the location of	un la dinerchandre
	Laboration and the second state	A. In. Colorent, b. A tute alder &	a weiter den der der si	in the life has been a first of the	(Intel   Intel & A
-60					
-80					
-100					

**Figure 4.** Generate channel-coded signals to evaluate the throughput of your receiver with Keysight signal generators and PWSG for NR-V2X application's advanced capabilities.



Testing of Receiver Hardware:

- Create 3GPP standard compliant NR-V2X signals for V2X direct communication using PC5 interface
- Quickly configure and generate Fixed Reference Channels (FRC)
- Create V2X signals with channel-coded PSSCH, PSCCH, and PSFCH for BLER and BER tests
- Support retransmission

FRC Configuration (38.521 v17.4.1)				
FRC Type	FRC for receiver requirements for QPSK		~	
Bandwidth	FR1 10MHz		~	
Subcarrier Spacing	15 kHz		~	
		ок	Cancel	
		UK	Caller	

Figure 5. NR-V2X FRC Configuration Wizard



# **PWSG for NR-V2X Licensing**

PWSG for NR-V2X application offers a waveform playback license N7632EMBC. The license should be installed on the supported signal generator instrument.

- N7632EMBC is an embedded license installed on a supported signal generator, such as X-Series Signal Generator, VXT or VXG, which enables you to generate, make a live connection to download and offline playback NR-V2X waveforms. N7632EMBC is recommended for design and verification or manufacturing teams.
- Instrument license mode: each instrument needs a valid license (N7632EMBC) to playback waveforms. Waveforms can be saved in signal generators for offline playback.

Capabilities	N7632EMBC support
Sidelink channels and signals: PSCCH, PSSCH, PSFCH, CSI-RS, PSSCH-PTRS	Y
Sidelink SSBlock: S-SS and PSBCH with MIB auto generation	Y
Support both single carrier and multi-carrier	Y
Subcarrier Spacing: FR1: 15 kHz, 30 kHz, 60 kHz; FR2: 60 kHz, 120 kHz	Y
Carrier bandwidth (MHz): FR1: 5, 10, 15, 20, 25, 30, 40, 50, 60, 70, 80, 90, 100; FR2: 50, 100, 200, 400	Y
Support retransmission	Y
Support FRC Config wizard	Y
PSSCH auto-detection based on SCI in PSCCH	Y
Support PSSCH-Second stage SCI	Y
Support Phase Tracking Reference Signal (PTRS)	Y
Multiple BWPs in single carrier	Y
Support Time Scale Factor	Y
MCS Table 5.1.3.1-1/2/3 for PSSCH	Y
Payload data (PN9/15/23/31, Custom Bit Pattern, or User File)	Y
Export waveform files (encrypted Signal Studio waveform file)	Y
Live Connection to X-Series Signal Generators, PXIe VXT and VXG	Y
Offline waveform file playback	Y
IQ/Spectrum/CCDF Plots	Y

#### **PWSG for NR-V2X feature summary**

#### **Supported standards**

Specification	Name	Version	Date
3GPP TS38.211	Physical channels and modulation	16.8.0	2021.12
3GPP TS38.212	Multiplexing and channel coding	16.8.0	2021.12
3GPP TS38.213	Physical layer procedures for control	16.8.0	2021.12
3GPP TS38.214	Physical layer procedures for data	16.8.0	2021.12
3GPP TS38.101-1	NR; User Equipment (UE) radio transmission and reception; Part 1: Range 1 Standalone	17.4.1	2022.07
3GPP TS38.521-1	NR; User Equipment (UE) conformance specification; Radio transmission and reception; Part 1: Range 1 standalone	17.4.1	2022.07



# **Ordering Information**

# Software licensing and configuration

PWSG Desktop application offers flexible licensing options, including:

- Node-locked: Allows you to use the license on one specified instrument/computer.
- Transportable: Allows you to use the license on one instrument/computer at a time. This license may be transferred to another instrument/computer using Keysight's online tool.
- Floating: Allows you to access the license on networked instruments/computers from a server, one at a time. For concurrent access, multiple licenses may be purchased. Floating support single site, single region and worldwide three different types.
- USB portable: Allows you to move the license from one instrument/computer to another by end-user only with certified USB dongle, purchased separately.
- Subscription (Time-based): License is time limited to a defined period, such as 6, 12, 24 or 36 months

#### PathWave signal generation for NR-V2X N7632EMBC license

Waveform	Playback License (N7632EMBC)	

Software license type	Software license	KeysightCare subscription
Node-locked perpetual	R-Y5B-001-A	R-Y6B-001-y <sup>2</sup>
Node-locked time-based	R-Y4B-001-z <sup>1</sup>	Included
Transportable perpetual	R-Y5B-004-D	R-Y6B-004-y <sup>2</sup>
Transportable time-based	R-Y4B-004-z <sup>1</sup>	Included

One-month KeysightCare Support and Subscription		
Support subscription Description		
R-Y6B-001	1-month of support subscription for node-locked perpetual licenses	
R-Y6B-504	1-month of support subscription for transportable perpetual license	

1. z means different time-based license duration. F for 6 months, L for 12 months, X for 24 months, and Y for 36 months. All timebased licenses have included the support subscription same as the time-base duration.

 y means different support subscription duration. L for 12 months (as default), X for 24 months, Y for 36 months, and Z for 60months. Support subscription must be purchased for all perpetual licenses with 12-months as the default. All software upgrades and KeysightCare support are provided for software licenses with valid support subscription.

3. Support subscription for all perpetual licenses can be extended with monthly extensions.



# Hardware configurations

To learn more about compatible hardware and required configurations, please visit:

www.keysight.com/find/SignalStudio\_platforms

## **PC requirements**

A PC is required to run PWSG Desktop. www.keysight.com/find/SignalStudio\_pc

## **Websites**

#### www.keysight.com/find/PWSG

PathWave Signal Generation for NR-V2X

NR-V2X Waveform Creation and Offline Playback: www.keysight.com/find/N7632EMBC

Comprehensive Online Documentation: <a href="http://www.keysight.com/find/signalstudio\_support">www.keysight.com/find/signalstudio\_support</a> PathWave Signal Creation Desktop Software: <a href="http://www.keysight.com/find/PWSG\_software">www.keysight.com/find/PWSG\_software</a>

### Literatures

PathWave Signal Generation, Brochure, <u>5989-6448EN</u> Signal Studio Pro for LTE V2X, Technical Overview, <u>5992-3826EN</u>

For more information on Keysight Technologies' products, applications, or services, please visit: www.keysight.com



This information is subject to change without notice.© Keysight Technologies, 2022, Published in USA, September 19, 2022, 3122-1883.EN