



8302

Max Continuous Output Current: 65A RMS
Surge Rating: 2X power at up to 200 V_p or 150A
Apparent Power Rating: Up to 5X continuous power rating at up to 200 V_p or 65A
Supply Voltage: 120V ±10% 20A, 208V ±10% 20A, or 240V ±10% 20A, 50/60Hz
Dimensions (HxWxD): 5.25 x 19.0 x 25.26 in. (13.34 x 48.26 x 64.16 cm)
Weight: 84 lbs. (38.1 kg)



8304

Max Continuous Output Current: 115A RMS
Surge Rating: 2X power at up to 200 V_p or 300A
Apparent Power Rating: Up to 5X continuous power rating at up to 200 V_p or 115A
Supply Voltage: Three-phase, 208V ±10%, 20A, 50/60 Hz; 400V ±10%, 20A version available.
Dimensions (HxWxD): 35.05 x 22.56 x 31.56 inches (89.03 x 57.3 x 80.16 cm)
Weight: Appx. 290 lbs. (131.5 kg)



8306

Max Continuous Output Current: 180A RMS
Surge Rating: 2X power at up to 200 V_p or 450A
Apparent Power Rating: Up to 5X continuous power rating at up to 200 V_p or 175A
Supply Voltage: Three-phase, 208V ±10%, 20A, 50/60 Hz; 400V ±10%, 20A version available.
Dimensions (HxWxD): 35.05 x 22.56 x 31.56 inches (89.03 x 57.3 x 80.16 cm)
Weight: Appx. 370 lbs. (167.8 kg)



8308

Max Continuous Output Current: 240A RMS
Surge Rating: 2X power at up to 200 V_p or 600A
Apparent Power Rating: Up to 5X continuous power rating at up to 200 V_p or 230A
Supply Voltage: Three-phase, 208V ±10%, 40A, 50/60 Hz; 400V ±10%, 40A version available.
Dimensions (HxWxD): 42.05 x 22.56 x 31.56 inches (106.81 x 57.3 x 80.16 cm)
Weight: Appx. 460 lbs. (208.7 kg)



8310

Max Continuous Output Current: 300A RMS
Surge Rating: 2X power at up to 200 V_p or 750A
Apparent Power Rating: Up to 5X continuous power rating at up to 200 V_p or 290A
Supply Voltage: Three-phase, 208V ±10%, 40A, 50/60 Hz; 400V ±10%, 40A version available.
Dimensions (HxWxD): 45.80 x 22.56 x 31.56 inches (116.33 x 57.3 x 80.16 cm)
Weight: Appx. 540 lbs. (244.9 kg)

Note: 8304, 8306, 8308 and 8310 model dimensions and weights are subject to change.



8504

Max Continuous Output Current: 80A RMS
Surge Rating: 2X power at up to 400 V_p or 150A
Apparent Power Rating: Up to 5X continuous power rating at up to 400 V_p or 150A
Supply Voltage: Single-phase, 208V ±10%, 30A, 50/60 Hz; 230V/240V ±10%, 30A version available
Dimensions (HxWxD): 5.25 x 19.0 x 25.26 in. (13.34 x 48.26 x 64.16 cm)
Weight: 84 lbs. (38.1 kg)



8508

Max Continuous Output Current: 160A RMS
Surge Rating: 2X power at up to 400 V_p or 300A
Apparent Power Rating: Up to 5X continuous power rating at up to 400 V_p or 300A
Supply Voltage: Three-phase, 208V ±10%, 30A, 50/60 Hz; 400V ±10%, 30A version available.
Dimensions (HxWxD): 35.05 x 22.56 x 31.56 inches (89.03 x 57.3 x 80.16 cm)
Weight: Appx. 290 lbs. (131.5 kg)



8512

Max Continuous Output Current: 240A RMS
Surge Rating: 2X power at up to 400 V_p or 450A
Apparent Power Rating: Up to 5X continuous power rating at up to 400 V_p or 450A
Supply Voltage: Three-phase, 208V ±10%, 30A, 50/60 Hz; 400V ±10%, 30A version available.
Dimensions (HxWxD): 35.05 x 22.56 x 31.56 inches (89.03 x 57.3 x 80.16 cm)
Weight: Appx. 370 lbs. (167.8 kg)



8516

Max Continuous Output Current: 320A RMS
Surge Rating: 2X power at up to 400 V_p or 600A
Apparent Power Rating: Up to 5X continuous power rating at up to 400 V_p or 600A
Supply Voltage: Three-phase, 208V ±10%, 60A, 50/60 Hz; 400V ±10%, 60A version available.
Dimensions (HxWxD): 42.05 x 22.56 x 31.56 inches (106.81 x 57.3 x 80.16 cm)
Weight: Appx. 460 lbs. (208.7 kg)



8520

Max Continuous Output Current: 400A RMS
Surge Rating: 2X power at up to 400 V_p or 750A
Apparent Power Rating: Up to 5X continuous power rating at up to 400 V_p or 750A
Supply Voltage: Three-phase, 208V ±10%, 60A, 50/60 Hz; 400V ±10%, 60A version available.
Dimensions (HxWxD): 45.80 x 22.56 x 31.56 inches (116.33 x 57.3 x 80.16 cm)
Weight: Appx. 540 lbs. (244.9 kg)



8524

Max Continuous Output Current: 480A RMS
Surge Rating: 2X power at up to 400 V_p or 900A
Apparent Power Rating: Up to 5X continuous power rating at up to 400 V_p or 900A
Supply Voltage: Three-phase, 208V ±10%, 60A, 50/60 Hz; 400V ±10%, 60A version available.
Dimensions (HxWxD): 51.05 x 22.56 x 31.56 inches (129.67 x 57.3 x 80.16 cm)
Weight: Appx. 620 lbs. (281.2 kg)

Note: 8508, 8512, 8516, 8520 and 8524 model dimensions and weights are subject to change.



8704

Max Continuous Output Current: 60A RMS
Surge Rating: 2X power at up to 400 V_p or 150A
Apparent Power Rating: Up to 5X continuous power rating at up to 400 V_p or 150A
Supply Voltage: Single-phase, 208V ±10%, 30A, 50/60 Hz; 230V/240V ±10%, 30A version available
Dimensions (HxWxD): 5.25 x 19.0 x 25.26 in. (13.34 x 48.26 x 64.16 cm)
Weight: 84 lbs. (38.1 kg)



8708

Max Continuous Output Current: 120A RMS
Surge Rating: 2X power at up to 400 V_p or 300A
Apparent Power Rating: Up to 5X continuous power rating at up to 400 V_p or 300A
Supply Voltage: Three-phase, 208V ±10%, 30A, 50/60 Hz; 400V ±10%, 30A version available.
Dimensions (HxWxD): 35.05 x 22.56 x 31.56 inches (89.03 x 57.3 x 80.16 cm)
Weight: Appx. 290 lbs. (131.5 kg)



8712

Max Continuous Output Current: 180A RMS
Surge Rating: 2X power at up to 400 V_p or 450A
Apparent Power Rating: Up to 5X continuous power rating at up to 400 V_p or 450A
Supply Voltage: Three-phase, 208V ±10%, 30A, 50/60 Hz; 400V ±10%, 30A version available.
Dimensions (HxWxD): 35.05 x 22.56 x 31.56 inches (89.03 x 57.3 x 80.16 cm)
Weight: Appx. 370 lbs. (167.8 kg)



8716

Max Continuous Output Current: 240A RMS
Surge Rating: 2X power at up to 400 V_p or 600A
Apparent Power Rating: Up to 5X continuous power rating at up to 400 V_p or 600A
Supply Voltage: Three-phase, 208V ±10%, 60A, 50/60 Hz; 400V ±10%, 60A version available.
Dimensions (HxWxD): 42.05 x 22.56 x 31.56 inches (106.81 x 57.3 x 80.16 cm)
Weight: Appx. 460 lbs. (208.7 kg)



8720

Max Continuous Output Current: 300A RMS
Surge Rating: 2X power at up to 400 V_p or 750A
Apparent Power Rating: Up to 5X continuous power rating at up to 400 V_p or 750A
Supply Voltage: Three-phase, 208V ±10%, 60A, 50/60 Hz; 400V ±10%, 60A version available.
Dimensions (HxWxD): 45.80 x 22.56 x 31.56 inches (116.33 x 57.3 x 80.16 cm)
Weight: Appx. 540 lbs. (244.9 kg)



8724

Max Continuous Output Current: 360A RMS
Surge Rating: 2X power at up to 400 V_p or 900A
Apparent Power Rating: Up to 5X continuous power rating at up to 400 V_p or 900A
Supply Voltage: Three-phase, 208V ±10%, 60A, 50/60 Hz; 400V ±10%, 60A version available.
Dimensions (HxWxD): 51.05 x 22.56 x 31.56 inches (129.67 x 57.3 x 80.16 cm)
Weight: Appx. 620 lbs. (281.2 kg)